

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 IPC-B2B40-ZS	1/3" 4Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 2.8~12mm varifocal lens, Max. IR LEDs Length 40m Support Smart IR, Micro SD card memory, IP67, PoE		16,700,000
2 EZ-IPC-B1B40P EZ-IP 2	1/3" 4Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 3.6mm fixed lens, Max. IR LEDs Length 30m Support Smart IR, IP67, PoE		12,500,000
3 EZ-IPC-B1B20P-L EZ-IP 2	1/2.7" 2Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@1080P(1920×1080) & 25/30fps@1.3MP(1280×960) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 3.6mm fixed lens, Max. IR LEDs Length 30m Support Smart IR, IP67, PoE		8,900,000
4 EZ-IPC-T1B40P EZ-IP 2	1/3" 4Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 3.6mm fixed lens, Max. IR LEDs Length 30m Support Smart IR, IP67, PoE		12,500,000
5 EZ-IPC-T1B20P-L EZ-IP 2	1/2.7" 2Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@1080P(1920×1080) & 25/30fps@1.3MP(1280×960) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 3.6mm fixed lens, Max. IR LEDs Length 30m Support Smart IR, IP67, PoE		8,900,000
6 IPC-B1A30	1/3" 3Megapixel progressive scan CMOS H.264+/H.264 dual-stream encoding 20fps@3M(2048×1536)&25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens, Max. IR LEDs Length 30m, IP67, PoE		8,300,000
7 IPC-B2A30	1/3" 3Megapixel progressive scan CMOS H.264+/H.264 dual-stream encoding 20fps@3M(2048×1536)&25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7~12mm Motorized lens, Micro SD card slot, up to 128GB Max. IR LEDs Length 60m, IP67, PoE		16,500,000
8 IPC-D2B40-ZS	1/3" 4Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 2.8~12mm varifocal lens, Max. IR LEDs Length 30m Support Smart IR, Micro SD card memory, IP67, PoE		16,500,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
9 IPC-T1A30	1/3" 3Megapixel progressive scan CMOS H.264+/H.264 dual-stream encoding 20fps@3M(2048x1536)&25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens, Max. IR LEDs Length 30m, IP67, PoE		8,300,000
10 IPC-D1A30	1/3" 3Megapixel progressive scan CMOS H.264+/H.264 dual-stream encoding 20fps@3M(2048x1536)&25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens, Max. IR LEDs Length 30m, IP67, IK10, PoE		8,600,000
11 NVR1A04HS-4P	4 channel IP camera input, 1/4/8/9 channel Live Preview H.264+/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 6MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 Support 4PoE port, 100 Mbps Network Card, P2P support		12,500,000
12 NVR1A08HS	8 channel IP camera input, 1/4/8/9 channel Live Preview H.264+/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 6MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support		7,400,000








EZ-IP






Surveillance Made Simple














مدل ردیف	مشخصات فنی	تصویر	قیمت
1 DH-PSD81602-A360	8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10		Call
2 DH-PSD8802-A180	4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10		Call

مدل ردیف	مشخصات فنی	تصویر	قیمت
3 IPC-PFW8800-A180	<p>4x2MP Multi-Sensor Panoramic Network IR Bullet Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/2 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
4 IPC-PFW8601-A180	<p>3x2MP Multi-Sensor Panoramic Network IR Bullet Camera Three 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x832, 3.6mm fixed lens Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
5 DH-IPC-PDBW8800-A180	<p>4x2MP Multi-Sensor Panoramic Network IR Dome Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
6 DHI-ITC237-PW1B-IRZ	<p>دوربین ANPR با قابلیت تشخیص پلاک، مناسب برای ورودی های پارکینگ 2 Megapixel Full HD WDR Access ANPR Camera -Embedded with LPR algorithm inside the camera -plate cutout, snapshot preview, recording -White list database,1 ch relay out to control the barrier performance for outdoor applications· 1/2.8" 2Megapixel progressive scan CMOS H.265/H.264M/H.264H/H.264B dual-stream encoding 25/30fps@1080P(1920×1080), 2.7mm~12mm Motorize lens WDR(140dB),BLC,HLC,Day/Night(ICR),3DNR,AWB,AGC,BLC Mirco SD card 64GB, IR Distance 3~8m, IP67, IK10, PoE</p>		82,000,000
7 DH-IPC5831EP-ZE	<p>1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) 2.7mm ~12mm motorized lens, Max. Aperture F1.6 WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory , 128 GB 1/1 Audio In/Out, 2/1 Alarm In/Out Max. IR LEDs Length 50m , Smart IR, IP67,IK10, PoE (Tripwire Intrusion Object Abandoned/Missing Face)</p>		43,000,000








مدل ردیف	مشخصات فنی	تصویر	قیمت
8	<p>Ambarella™</p> <p>1/2.5" 8Megapixel progressive scan CMOS H.265+&H.265&H.264&MJPEG triple-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm & 2.8mm fixed lens, Max. IR LEDs Length 40m Micro SD card memory , 128 GB, IP67, PoE Smart Detection (Tripwire Intrusion Scene Change Face)</p> <p>ePoE</p>		27,500,000
9	<p>8MP Lite IR Vari-focal Starlight Bullet Network Camera 1/2.7" progressive scan CMOS image sensor, low illuminance, high image definition Smart H.265/H.264 codec, MJPEG, high compression rate, ultra-low bit rate 8MP (3840 × 2160) @15 fps, 2688×1520 @25/30 fps WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Regic of Interest, Voltage Detection 2.7 mm–13.5 mm Motorized fixed lens Max. IR LEDs Length 60m, Micro SD card memory , 256 GB IP67, PoE, Smart Detection (Tripwire Intrusion)</p>		32,100,000
10	<p>NEW Product</p> <p>ePoE</p> <p>6MP WDR IR Bullet Network Camera 1/2.9" 6Megapixel progressive scan STARVIS™ CMOS H.265&H.264 Triple-stream encoding 20fps@6M(3072×2048),25/30fps@4M(2688×1520) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 7mm~35mm(5x zoom) Motorized lens Max. IR LEDs Length 100m, Micro SD card memory , 128 GB 2/1 Alarm in/out, 1/1 audio in/out, IP67, IK10, PoE (Tripwire Intrusion Object Abandoned Missing Face)</p>		41,000,000
11	<p>Ambarella™</p> <p>ePoE</p> <p>1/2.9" 6Megapixel progressive scan STARVISTM CMOS H. 265+ & H.265 & H.264+ & H.264 triple-stream encoding 20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens, Max. IR LEDs Length 40m Micro SD card memory , 128 GB, IP67, PoE (Tripwire Intrusion Object Abandoned/Missing Face)</p>		23,800,000
12	<p>1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 15fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card 128GB, Max IR LEDs Length 60m ,Smart IR IP67, PoE, Smart Detection (Tripwire Intrusion)</p>		28,300,000
13	<p>1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 & MJPEG triple-stream encoding Max 20fps@4Mp(2560×1440),25/30fps@3M(2304x1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens, Max. IR LEDs Length 50m Micro SD card memory , 128 GB, Audio in/Out, Alarm In/Out IP67, PoE, (Tripwire Intrusion Scene Change Face)</p>		27,500,000
14	<p>Ambarella™</p> <p>NEW Product</p> <p>ePoE</p> <p>4MP Pro AI IR Vari-focal, 1/1.8" 4Megapixel progressive scan CMOS H.265,H.264,H.264B,H.264H, MJPEG triple-stream encoding Max 25/30fps@4Mp(2688×1520), 50/60fps@2Mp(1920 × 1080) WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm-32mm Motorized lenz, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 Smart Detection Tripwire, intrusion (Recognition of vehicle and people), Object Abandoned / Missing, fast moving, loitering detection, parking detection and people gathering Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection, Scene Change, Heatmap, IP67, IK10, PoE</p>		43,000,000







15	DH-IPC-HFW5431EP-ZE	  NEW Product	<p>4MP WDR IR Bullet Network Camera 1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25/30fps@4Mp(2688×1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 IP67, IK10, PoE, (Tripwire Intrusion Object Abandoned / Missing Face)</p>		35,000,000
16	DH-IPC-HFW5231EP-Z12E	 	<p>1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding 50/60fps@1080(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 5.3mm ~ 64mm 12x zoom lens 1/1 Audio in/Out, 2/1 Alarm In/Out Micro SD card up to 128 GB, Max. IR LEDs Length 200m , Smart IR IP67, IK10, PoE, (Tripwire Intrusion Object Abandoned/Missing Face)</p>		40,000,000
17	DH-IPC-HFW5231EP-ZE	 	<p>1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 & MJPEG triple-stream encoding 50/60fps@1080(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~ 13.5mm motorized lens 1/1 Audio in/Out, 2/1 Alarm In/Out Micro SD card memory , 128 GB, Max. IR LEDs Length 50m , Smart IR IP67, IK10, PoE, Smart Detection (Tripwire Intrusion Object Abandoned/Missing Face)</p>		34,000,000
18	DH-IPC-HFW4431T-ASE	  NEW Product	<p>4MP WDR IR Mini Bullet Network Camera 1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25/30fps@4Mp(2688×1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC,ROI 3.6mm Fixed lens, Max. IR LEDs Length 80m, Smart IR Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 1/1 IP67, IK10, PoE, (Tripwire Intrusion Object Abandoned / Missing Face)</p>		19,500,000
19	DH-IPC-HFW4431DP-BAS-H	Eco-Savvy Lite	<p>1/3" 4Megapixel progressive scan CMOS 3.6mm fixed lens Max 20fps@4M(2592×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 & MJPEG triple stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Smart Detection supported Face Detection, Tripwire, Intrusion, Object Abandoned/Missing 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 80m, Mirco SD card 128GB, IP67, PoE</p>		Discontinue
20	DH-IPC-HFW4431BP-BAS-H	Eco-Savvy Lite	<p>1/3" 4Megapixel progressive scan CMOS 3.6mm fixed lens Max 20fps@4M(2592×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 & MJPEG triple stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Smart Detection supported Face Detection, Tripwire, Intrusion, Object Abandoned/Missing 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 50m, Mirco SD card 128GB, IP67, PoE</p>		Discontinue

مدل ردیف	مشخصات فنی	تصویر	قیمت
21	<p>Eco-Savvy Lite</p> <p>DH-IPC-HFW2431TP-ZS</p> <p>1/3" 4 Megapixel progressive CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 20fps@4M(2688×1520)&25/30fps@3M(2304×1296) 2.7mm ~13.5mm motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory , 128 GB Max. IR LEDs Length 60m , Smart IR IP67, PoE+, Smart Detection (Tripwire Intrusion)</p>		25,500,000
22	<p></p> <p>DH-IPC-HFW1431SP</p> <p>1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 20fps@4M(2688×1520) &25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, PoE</p>		16,800,000
23	<p></p> <p>DH-IPC-HFW4231EP-S</p> <p>1/2.8" 2Megapixel progressive scan STARVIS™ CMOS(Starlight) 3.6mm fixed lens 50/60fps@1080P(1920×1080) H.265+/H.265/H.264+/H.264 triple-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Smart Detection supported: Face Detection, Tripwire, Intrusion, Object Abandoned/Missing Max. IR LEDs Length 40m, Mirco SD card 128GB, IP67, PoE</p> <p></p>		19,000,000
24	<p>4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor, low illuminance, high image definition H.265 codec, high compression rate, ultra-low bit rate 25/30fps@4MP(2560 × 1440), Max. supports 4MP (2688 × 1520)@20 fps WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 3.6mm Fixed lens, Max. IR LEDs Length 30m, Smart IR IP67, PoE, Micro SD card memory , 256 GB Smart Detection (Tripwire Intrusion)</p> <p></p>		14,100,000
25	<p>2MP WDR IR Bullet Network Camera 1/2.8" 2Megapixel progressive Starvis™ CMOS H.265+/H.265/H.264+/H.264 Double-stream encoding 25/30fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 2.7mm~13.5mm, Max. IR LEDs Length 60m, Smart IR Micro SD card memory , 128 GB, Audio I/O 1/1, Alarm I/O 1/1 IP67, IK10(Optional), PoE, (Tripwire Intrusion Scene Change)</p> <p></p>		23,800,000
26	<p>DH-IPC-HFW1320SP</p> <p>1/3" 3Megapixel progressive scan CMOS H.264+/H/264 dual-stream encoding Max 20fps@3M(2048× 1536)&25/30fps@1080P(1920× 1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens, Max. IR LEDs Length 30m, IP67, PoE</p>		11,200,000
27	<p>DH-IPC-HFW1231SP</p> <p>1/2.8" 2Megapixel progressive CMOS, Starlight H.265& H.264 dual-stream encoding 25/30fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 2.8mm fixed lens, Max. IR LEDs Length 30m, Smart IR IP67, PoE, Smart Detection (Tripwire Intrusion)</p>		12,800,000
28	<p>DH-IPC-HFW1230SP</p> <p>1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens, Max. IR LEDs Length 30m, IP67, PoE</p>		10,650,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت
29	HDBW-5831EP-ZE  	1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160),25/30fps@3M(2304×1296) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~ 12mm motorized lens 1/1 Audio in/Out, 1/1 Alarm In/Out Micro SD card memory , 128 GB Max. IR LEDs Length 50m , Smart IR IP67, IK10, PoE+, (Tripwire Intrusion Object Abandoned/Missing Face)		43,000,000
30	DH-IPC-HDBW5431EP-Z-H	1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 & MJPEG triple-stream encoding Max 20fps@4Mp(2560×1440),25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens, Max. IR LEDs Length 50m IP67,IK10, PoE, Micro SD card memory , 128 GB Audio in/Out, Alarm In/Out Smart Detection (Tripwire Intrusion Scene Change Face)		27,500,000
31	DH-IPC-HDBW4831EP-ASE 	1/2.5" 4K progressive scan Starvis CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens, Max. IR LEDs Length 30m Alarm in/out, Audio in/out Micro SD card memory , 128 GB, IP67,IK10, PoE Smart Detection (Tripwire Intrusion Scene Change Object Abandoned/Missing Face)		27,500,000
32	DH-IPC-HDW4831EMP-ASE 	1/2.5" 4K progressive scan CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens, Max. IR LEDs Length 50m Built-in Mic , Micro SD card memory , 128 GB IP67,PoE, (Tripwire Intrusion Scene Change Object Abandoned/Missing Face)		27,500,000
33	HDW4631EM-ASE  Eco-Savvy 	1/2.9" 6Megapixel progressive scan STARVISTM CMOS H. 265+ & H.265 & H.264+ & H.264 triple-stream encoding 20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens, Built-in Mic Max. IR LEDs Length 50m, Smart IR Micro SD card memory , 128 GB, IP67, PoE (Tripwire Intrusion Object Abandoned/Missing Face)		23,800,000
34	DH-IPC-HDW4431EM-ASE  Eco-Savvy Lite	1/3" 4Megapixel progressive scan CMOS 2/8 and 3.6mm fixed lens Max 20fps@4M(2592×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 & MJPEG triple stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Smart Detection supported, Built-in Mic Face Detection,Tripwire, Intrusion, Object Abandoned/Missing Max. IR LEDs Length 50m, Mirco SD card 128GB, IP67, PoE		19,500,000
35	DH-IPC-HDW4431EP-ASH Eco-Savvy Lite	1/3" 4Megapixel progressive scan CMOS 3.6mm fixed lens, 25/30fps@4M(2688×1520) H.265+/H.265/H.264+/H.264 & MJPEG triple stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Smart Detection supported, Built-in Mic Face Detection,Tripwire, Intrusion, Object Abandoned/Missing Max. IR LEDs Length 50m, Mirco SD card 128GB, IP67, PoE		Discontinue

مدل ردیف	مشخصات فنی	تصویر	قیمت
36	 <p>1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 20fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Mirco SD card 128GB Max IR LEDs Length 30m ,Smart IR IP67,IK10, PoE</p>		28,300,000
37	<p>1/3" 4Megapixel progressive CMOS 2.7~13.5mm Motorized lens 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Mirco SD card 128GB, Max IR LEDs Length 50m, IP67,IK10, PoE</p>		25,500,000
38	 <p>1/3" 4Megapixel progressive CMOS, 3.6mm fixed lens 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE</p>		16,900,000
39	 <p>1/3" 4Megapixel progressive CMOS, 2.8mm fixed lens 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, PoE</p>		16,800,000
40	<p>1/3" 3Megapixel progressive scan CMOS, 3.6mm fixed lens H.264+/H/264 dual-stream encoding Max 20fps@3M & 25/30fps@1080P DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, Micro SD card Memory , 128 GB Audio In/Out, IP67, IK10, PoE</p>		11,300,000
41	<p>1/2.7" 2Megapixel progressive scan CMOS, 2.8mm fixed lens H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, PoE</p>		10,650,000
42	<p>1/2.7" 2Megapixel progressive scan CMOS, 3.6mm fixed lens H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE</p>		10,850,000
43	<p>1/2.7" 2MP CMOS Sensor, 2.7mm ~ 11mm , 4x Optical Zoom H.264+/H.264 Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 100°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in Mic, IR Distance up to 30m, POE, (Tripwire Intrusion Scene Change Face Abandoned-Missing Object)</p>		29,000,000
44	<p>1/2.8" 2MP STARVIS™ CMOS (Starlight) H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 25/30fps@1080P, 2.7mm ~ 8.1mm , 3x Optical Zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max Pan: 80° /s; Tilt: 40° /s speed Pan: 0° ~ 355°; Tilt: 5° ~ 90° rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, Support Defog, IR Distance up to 15m, IP 66, support POE (Tripwire Intrusion Abandoned/Missing Face Detection)</p>		31,000,000





مدل ردیف	مشخصات فنی	تصویر	قیمت
45 DH-SD6CE230U-HNI	<p>1/2.8" 2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P 4.5mm~135mm Powerful 30x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map), Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm 7/2 in/out, Audio 1/1 in/out, 1*Video output RS485, IR Distance up to 200m, PoE+, IP67, IK10</p>		134,900,000
46 DH-SD6CE225U-HNI	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 50/60fps@1080P, 4.8mm~120mm 25x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC Support Defog, ROI, EIS, Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 Alarm 7/2 in/out, Audio 1/1 in/out IR Distance up to 200m, PoE+, IP67, IK10</p>		92,700,000
47 DH-SD49225XA-HNR	<p>2MP 25x Starlight IR PTZ AI Network Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max. 1~60fps@1080P,960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p>		76,500,000
	NEW Product		
48 DH-SD49225T-HN	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 25/30fps@1080P, 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Support Defog IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm 2/1 in/out, Audio 1/1 in/out Support PoE+, IR Distance up to 100m, IP66</p>		67,000,000
49 DH-SD65F230F-HNI	<p>1/1.9" 2MP CMOS Sensor(Super Starlight) H.264 / MJPEG Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P 6mm~180mm Powerful 30x optical zoom Max 300°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Support Defog, ROI, EIS Alarm 7/2 in/out, Audio 1/1 in/out, 1 video output RS485, IR Distance up to 100m, Support PoE+, IP66,IK10</p>		Call
	Super Starlight		





50	DH-SD59225U-HNI	<p>2MP 25x Starlight IR PTZ Network Camera 1/2.8" Exmor R CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.8mm~120mm 25x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection), Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out Support PoE+, IR Distance up to 150m, IP66,OSD</p>		85,200,000
51	DH-SD59230U-HNI	<p>2MP 30x Starlight IR PTZ Network Camera 1/2.8" Exmor R CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.5mm~135mm 30x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection), Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out Support PoE+, IR Distance up to 150m, IP66,OSD</p>		125,500,000
52	DH-SD59430U-HNI	<p>1/3" CMOS Sensor H.265+/H.265/H.264+/H.264 Encoding, Ultra-low bit rate Max. 25/30fps@4M(2592×1520) & 50/60fps @1080P resolution WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out, Alarm In/Out, IP66, POE+ IR Distance up to 100m(AC24V)/ 80m(DC12V) Smart Detection (Tripwire Intrusion Scene Change Face Anandoned-Missing Object)</p>		139,000,000
53	DH-SD60230T-HN	<p>1/2.8" 2Mp CMOS Sensor H.264+/H.264 Encoding, Ultra-low bit rate transmission Max. 30fps@1080P(2592×1520) & 60fps @720P resolution DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 600°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out, Alarm In/Out IP67,IK10, POE+, (Tripwire Intrusion Scene Change Face Anandoned-Missing Object)</p>		Call
54	DHI-NVR2104HS-4KS2	<p>4 channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		10,700,000
55	DHI-NVR2104HS-P-4KS2	<p>4 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 4PoE Port, P2P support</p>		15,700,000

56	DH-NVR2108HS-4KS2	<p>8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		12,500,000
57	DH-NVR-2108HS-8P-4KS2	<p>8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 8Port PoE, P2P support</p>		22,000,000
58	DH-NVR4108HS-4KS2	<p>8 channel IP camera input 1/4/8/9 channel Live Preview, 8CH Playback H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		15,600,000
59	DH-NVR4116HS-4KS2	<p>16 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		21,500,000
60	DH-NVR4216-4KS2	<p>16 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*10/100/1000Mbps Mbps Network Card, P2P support</p>		32,600,000
61	DH-NVR4232-4KS2	<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*10/100/1000Mbps Mbps Network Card, P2P support</p>		35,700,000
62	DH-NVR5232-4KS2	<p>32 channel IP camera input, 32 channel Live Preview Up to 12Mp resolution preview&playback Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Max 320Mbps incoming bandwidth Record Rate 320 Mbps , 16 channel playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding HDMI/VGA simultaneous video output Support 2 SATA HDDs up to 20TB, 2 USB(1 USB3.0) 1000 Mbps Network Card , RS232, RS485 4 Alarm Input, 2 Relay Output, Support P2P</p>		55,000,000

63	DH-NVR4432-4KS2	<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 4 SATA HDD up to 6TB, 2 USB Ports (1 USB2 & 1 USB3) 16 Alarm Input, 4 Relay Output, RS232 , RS485 2*10/100/1000Mbps Mbps Network Card, P2P support</p>		47,800,000
64	DH-NVR5432-4KS2	<p>32 channel IPC input, 32 channel Live Preview Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2 HDMI/VGA simultaneous video output Support 4 SATA HDDs up to 40TB, 3 USB(1 USB3.0, 2USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485, 16 Alarm In , 6 Relay Output, P2P Support</p>		82,000,000
65	DH-NVR5464-4KS2	<p>64 channel IPC input, 64 channel Live Preview Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2 HDMI/VGA simultaneous video output Support 4 SATA HDDs up to 40TB, 3 USB(1 USB3.0, 2USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485, 16 Alarm In , 6 Relay Output, P2P Support</p>		102,000,000
66	DH-NVR4832-4KS2	<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 8 SATA HDD up to 6TB 3 USB Ports (2 USB2.0, 1 USB3.0) 16 Alarm Input, 4 Relay Output, RS232 , RS485 2*10/100/1000Mbps Mbps Network Card, P2P support</p>		82,500,000
67	DH-NVR5832-4KS2	<p>32 channel IPC input, 32 Channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback Max 16ch@1080P 4ch@4K H.265 H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232 16 Alarm In , 6 Relay Output, P2P Support, Raid 0/1/5/6/10</p>		110,000,000
68	DH-NVR5864-4KS2	<p>64 channel IPC input, 32 Channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback Max 16ch@1080P 4ch@4K H.265 H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 3 USB(1 USB3.0, 2USB2.0) 2*1000 Mbps Network Card, RS232 16 Alarm In , 6 Relay Output, P2P Support, Raid 0/1/5/6/10</p>		127,000,000

69	DH-NVR608-32-4KS2	<p>Intel Dual-core Processor, 32 channel IPC input, 32 Channel Live Preview (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding, Max 384Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232 , RS485, 16 Alarm In , 8 Relay Output</p>	117,000,000	
70	DH-NVR608-64-4KS2	<p>Intel Quad-core Processor 64 channel IPC input, 32 Channel Live Preview (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16), H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16 Alarm In , 8 Relay Output</p>	199,000,000	
71	DH-ESS1508C	<p>2U standard 19-inch rack case Connect master device via eSATA or USB 1 eSATA port transmission speed up to 3Gbps 1 USB 3.0 port data transmission higher than normal Powerful R / W performance: read >64MB/s, write >64MB/s ESS1508C: Max support Internal 8 SATA HDD up to 48TB Recommended with DVR, NVR connection</p>	45,800,000	
72	DH-PFS3006-4ET-60	<p>4-Port Fast Ethernet PoE Switch, Layer two commercial switch 2*10/100 Mbps Uplink ports, 4*10/100 Mbps PoE ports Port1≤60W, Port2-4≤30W, Total≤60W Support IEEE802.3af, IEEE802.3at(PoE+) ,Hi PoE 1.8Gbps Switching Capacity 890Kpps Mpps Packet Forwarding Rate 768Kb Packet Buffer Memory MAC atable size is 2K, Supports DC 48-57V power supply</p>	7,350,000	
73	DH-PFS3010-8ET-96	<p>8-Port Fast Ethernet PoE Switch, Layer two commercial switch 2*10/100/1000 Mbps Ports, 8*10/100 Mbps PoE Ports Port1≤60W, Port2-8≤30W, Total≤96W Support IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE 5.6Gbps Switching Capacity, 4.17 MppsPacket Forwarding Rate 4Mb Packet Buffer Memory MAC Table Size is 16K, Supports DC 48-57V power supply</p>	13,500,000	
74	DH-PFS3110-8P-96	<p>Two-layer industrial PoE switch 1*1000 Base-X, 1*10/100/1000 Base-T 8*10/100 Base-T (PoE power supply) Each POE power ≤30W, Total≤96W Support IEEE802.3af, IEEE802.3at standard 7.6G Switching Capacity, 4.17 MppsPacket Forwarding Rate 1Mb Packet Buffer Memory, Industrial wide temperature design MAC auto study and aging, MAC address list capacity is 8K</p>	16,800,000	

مدل ردیف	مشخصات فنی	تصویر	قیمت
75 DH-PFS4218-16ET-190	<p>Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤190W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity,5.36 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)</p>		42,500,000
76 DH-PFS4218-16ET-240	<p>Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤240W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity, 5.36 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)</p>		46,000,000
77 DH-PFS4226-24ET-240	<p>24-Port PoE Switch, Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 24*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤240W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity, 6.55 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)</p>		50,700,000
78 DH-PFS4226-24ET-360	<p>24-Port PoE Switch, Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 24*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤360W, Support PoE, PoE+, Hi-PoE 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity, 6.55 Mpps Packet Forwarding Rate Support Web management, Non-blocking video transmission management, PoE Setting/Event Statistics/Green PoE</p>		60,800,000

79	DH-PFS4226-24GT-360	<p>24-Port PoE Gigabit Managed Switch Layer 2 network management PoE switch 24*10/100/1000 Base-T (PoE power supply) 2*100/1000 Base-X, Port1/2 support Hi-PoE (60W) Each power ≤30W, PoE Budget≤360W Spanning tree: STP/RSTP/MSTP Network management based on SNMP Configuration: Web, Telnet, CLI Command Support Vlan:VLAN/802.1Q Standard Vlan, 8K MAC Table 52G Switching Capacity, 38.688 Mpps Packet Forwarding Rate EMC high protection design</p>		78,900,000
<p>NEW Product</p>				
80	PFT1300	<p>PoE Extender 1*10/100 Base-T PoE power receiving port 1*10/100 Base-T PoE power supply port, supply power for the next extender 1*10/100 Base-T PoE power supply port, supply power for IPC Support passive PoE cascade power supply and Ethernet data exchange Support IEEE 802.3af/at standard power supply IP Camera able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption ≤8W), maxtransmission distance 300m</p>		3,400,000
81	PFM700	<p>*1 Channel HDMI Transmission Signal *1080P/1080i/720P/576P/576i/480P/480i Resolution Output Signal , *60M (max)Transmission Distance *Input voltage DC5V *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video, signal:support HDMI 1.3</p>		9,500,000
82	DHI-NKB1000	<p>Keyboard to Control : Dahua High Speed Dome (all models) Dahua Standalone DVR , Dahua Network High Speed Dome Network Video Server Connection : RS485, RS422, USB, RS232 & Network Three Dimensional Joystick Control of PTZ Functions Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control, On-Screen Menu & User Operation Procedure Tips Connect to SmartPSS via USB</p>		44,000,000

